Specifications for Mitsubishi GOT

| Туре | | | GS2110-WTBD | GS2107-WTBD |
|--------------------|--|---|---|------------------------------|
| | Display device Screen size | | TFT color LCD 10" | 7" |
| | Resolutio n | dots | 800×480 | |
| Display section | Display size (WxH) | mm | 222×132.5 (horizontal format) | 154×85.9 (horizontal format) |
| | Number of characters Display color | | Freely definable 65536 colors | |
| | Backlight | | LED (not replaceable), Backlight off/screen saving time can be set. | |
| | Туре | | Analog resistive film | |
| | Key size | | Minimum 2×2 dots (per key) | |
| Touch panel | Simultaneous press | | Simultaneous press prohibited (only 1 point can be pressed) | |
| | Life | | 1 million times (operating force 0.98 N or less) | |
| Memory | C drive | | Flash memory (internal) (9 MB), for storing project data, OS | |
| | | | Life (no. of writings) 100,000 times | |
| | | | 1 ch, Transmission speed: 115200/57600/38400/19200/9600/4800bps | |
| | RS422 | Connector shape: D-Sub 9pin (female); Application: For communication with controllers | | |

Terminating resistor: 330 $\boldsymbol{\Omega}$ fixed

1 ch, Transmission speed: 115200/57600/38400/19200/9600/4800bps

RS232

Connector shape: D-Sub 9pin (male); Application: For communication with controllers and a barcode

reader, for connecting a personal computer (Project data read/write, FA transparent function)

Built-in interface

Data transfer method: 100BASE-TX, 10BASE-T, 1 ch, Connector shape: RJ-45 (modular jack);

Ethernet

Application: For communication with controllers, for connecting a personal computer

(Project data read/write, FA transparent function)

USB (Full Speed 12 Mbps), 1 ch, Connector shape: Mini-B;

USB

Application: For connecting a personal computer (Project data read/write, FA transparent function)

1 ch, Supported memory card: SDHC memory card, SD memory card;

SD card

Application: Project data read/write, logging data save

Buzzer output Single tone (LONG/SHORT/OFF adjustable)

Protective structure IP65F (Only the front part of the panel)

External dimensions mm 272x214x56 206x155x50

(WxHxD)

Weight Approx. 1.3 (excl. mounting Approx. 0.9 (excl. mounting

brackets) brackets)

Compatible software package GT Works3, version 1.105K or later* (English version)